



Good ventilation in pig and poultry houses is essential for both animal health and livestock efficiency.

On our website www.stienen.com you will find more information about our different ventilation solutions.

SGS

HIGH PRESSURE FAN



Ventilating with counter-pressure

- Low energy consumption in the control range
- Low-noise
- Stable pressure in the control range
- Suitable for central exhaust systems, air scrubbers and manure drying systems
- A suitable solution for every situation
- Appropriate protection grille available

STIENEN AGRI AUTOMATION

Stienen is a leading family company (1977) which has its roots in livestock farming. It is in our nature to be very close to our end users. We are a global supplier of innovative automation solutions for poultry and pig houses. Our climate solutions, automation systems, management software and the accompanying peripheral equipment are all developed and produced in-house.

Stienen
Mangaanstraat 9 - 6031 RT Nederweert
T +31 (0)495 - 63 29 26
E sales@stienen.com
www.stienen.com

STIENEN B3



SGS-L-EN25043

STIENEN B3



SGS high-pressure fans

Stienen SGS fans have been specially developed for easily controllable low-noise and energy-efficient ventilation, even with high counter-pressure.

This makes the SGS fans ideally suited for central exhaust systems, possibly in combination with air scrubbers and manure drying systems.

The fans (wall of fans) must always be positioned in front of the air scrubber.

Stienen supplies different versions of SGS fans enabling to provide the best suitable solution for each situation!

SPECIFICATIONS AQC

GENERAL

Max. 960 RPM
Low-noise level: i.e. 66 dB(A) with SGS-92H-D4S (measured on the blade's pressure side at a distance of 7m, under an angle of 45°)
Pressure-stable, also at low speeds
Available as ø 71, 82 and 92cm
Available with 0.75, 1.1, 1.5 or 2.2kW motors
With 2 or 4 blades
Protection grille available (obligatory with mounting heights < 2.7m)
Protection class: IP 56

AIRFLOW SGS IN M³/H

TYP	RPM	30Pa	40Pa	50Pa	60Pa	70Pa	100Pa	125Pa	150Pa	175Pa	200Pa	I-MAX
SGS-71H-A4X	960	16.090	15.990	15.550	15.130	14.180	13.950	x	x	x	x	2,3
SGS-82H-A2A	960	18.550	18.120	17.230	16.840	15.130	13.410	x	x	x	x	2,3
SGS-82H-C4E	960	23.150	22.610	22.510	22.290	21.970	21.550	20.690	19.830	17.266	x	4,0
SGS-92H-B2K	960	28.070	27.000	26.250	25.720	24.110	21.120	x	x	x	x	3,3
SGS-92H-C4R	960	28.210	27.970	27.430	26.840	26.500	25.820	x	x	x	x	4,0
SGS-92H-D4S	960	33.230	32.730	32.250	31.820	31.390	30.100	28.390	27.540	25.820	24.970	5,8

DIMENSIONS SGS IN MM

TYP	A	B	C	D	E	F	G
SGS-71H-VAR	729	716	730	747	x	430	x
SGS-71H	729	716	x	x	872	412	x
SGS-82H-VAR	818	802	818	835	x	430	x
SGS-82H	818	802	x	x	1000	412	x
SGS-92H-VAR	930	920	931	947	x	430	72
SGS-92H	930	920	x	x	1116	412	90

